Reflex Reflex NG 35, welded diaphragm expansion vessel, grey, 6/1.5 bar

Article number: 8270100





Features

| Туре | NG 35 |
|---|-----------|
| Colour | grey |
| Diaphragm material | SBR Butyl |
| Nominal volume | 35 I |
| Max. useful volume | 31.5 I |
| Max. permissible system temperature | 120 °C |
| Min. perm. operating temperature | -10 °C |
| max. perm. operating temperature | 70 °C |
| max. perm. operating pressure | 6 bar |
| Factory provided gas supply pressure | 1.5 bar |
| Connection | R 3/4" |
| Diameter | 354 mm |
| Height | 459 mm |
| High water connection | 130 mm |
| Tilt dimension approx. | 580 mm |
| Weight | 4.93 kg |

Description

Reflex Reflex NG 35

Diaphragm expansion tank for sealed heating and cooling water systems. Vessels are fitted according to Reflex company standard CS-004 based on DIN EN 13831. Approval according to Pressure Equipment Directive 2014/68/EC.

- durable epoxy resin coating
- welded design
- non-replaceable diaphragm according to DIN EN 13831
- vertical from 35 litres
- for antifreeze additive of at least 25 50 %
- with threaded connections
- max. permissible system temperature 120 °C
- permissible operating temperature 70 °C

