

TERMA MIRALL

Technical specifications / Tehnička specifikacija

Code / Šifra:	See table below Vidi tablicu niže
Description	vertical tube 68*12 mm horizontal tube 35 mm
Opis	vertikalna cijev 68*12 mm horizontalna cijev 35 mm
Connections	Middconnetion, 1x air vent, 1x blind plug
Priključci	priključak u sredini, 1x odzračni pipac, 1xčep
Accessories Pribor	wall brackets, air vent, plug, screws zidne konzole, odzračni pipac, čep, vijci
Operating pressure Radni tlak	3-6 Bar
Test pressure Ispitni tlak	8 Bar
Operating temp. Radna temperatura	max. 110 ° C



Code / Šifra	Hight / Visina A (mm)	Width / Širina B (mm)	Axes distance/ Razmak priključaka C (mm)	Depth/ Debljina (mm)	Pipe num. Broj Cijevi	Color Boja	Weight / težina KG	EN442 (Watt)	Rated thermal outputs / nazivna toplinska snaga	Thermal output in different operating Toplinska snaga u različitim uvjetima rada
G668047	1800	425	50	58	4+6	white / bijela	40,10	1266	Φ30=683W Φ50=1266W	$\Phi=11,2933 \cdot \Delta T^{1,2064}$
G668048	1800	425	50	58	4+6	crna / black	40,10	1304	Φ30=704W Φ50=1304W	$\Phi=11,6771 \cdot \Delta T^{1,2055}$

