


**IZJAVA O SVOJSTVIMA**  
**DECLARATION OF PERFORMANCE**






br. CPR\_01\_ACS



1. Jedinstveni identifikacijski kod vrste proizvoda: **suho prešane pločice, vodoupojnost  $E_v \leq 0,5\%$**   
Unique identification code of the product type: **dry-pressed ceramic tiles, with water absorption  $E_v \leq 0,5\%$**
2. Namjeravana(e) upotreba(e): **Za unutarnje i vanjske podne i zidne obloge**  
Intended use(s): **For internal and external floorings and walls**



3. Naziv ili registrirana robna marka te kontakt adresa proizvođača:  
Name or registered trade mark, and contact address of the manufacturer:  
**Ceramiche Atlas Concorde Spa, Via Canaletto 141 – 41042 Spezzano di Fiorano (MO) – ITALIJA**
4. Sustav(i) ocjenjivanja i provjere stalnosti svojstava: **Sustav 4**  
System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Naziv i identifikacijski broj akreditiranog laboratorija, ako je primjenjivo: **Nije primjenjivo**  
Name and identification number of notified laboratory, if relevant: **Not Relevant**

6. Deklarirana svojstva: Declared performances:

<b>Bitne karakteristike</b> <b>Essential Characteristics</b>	<b>Svojstvo</b> <b>Performance</b>	<b>Usklađena tehnička norma</b> <b>Harmonised Technical Specification</b>
<b>Reakcija na požar</b> <b>Reaction to Fire</b> 	<b>A1<sub>FL</sub>/A1</b>	<b>EN 14411</b>
<b>Emisija opasnih tvari:</b> <b>Release of dangerous substances:</b> 		
- Emisija kadmija – Cadmium	<b>NPD</b>	
- Emisija olova – Lead	<b>NPD</b>	
<b>Lomna čvrstoća (debljina ≥ 7,5mm):</b> <b>Breaking Strength (Thickness ≥ 7,5mm):</b> 	<b>≥ 1300N</b>	
<b>Klizavost:</b> <b>Slipperiness:</b> 	<b>Vidi priloženu tablicu</b> <b>See table attached</b>	
<b>Taktilnost:</b> <b>Tactility:</b>	<b>NPD</b>	
<b>Čvrstoća prijanjanja:</b> <b>Bond strength/adhesion:</b> 	<b>NPD</b>	

<b>Bitne karakteristike</b> <b>Essential Characteristics</b>	<b>Svojstvo</b> <b>Performance</b>	<b>Usklađena tehnička norma</b> <b>Harmonised Technical Specification</b>
<b>Otpornost na nagle promjene temperatura:</b> <b>Thermal shock resistance:</b> 	<b>udovoljava zahtjevima</b> <b>Pass</b>	<b>EN 14411</b>
<b>Izdržljivost, za: Durability, for:</b>  <b>- Unutarnji prostori:</b> <b>- Internal Use:</b>	<b>udovoljava zahtjevima</b> <b>Pass</b>	
<b>- Na otvorenom: Otpornost na smrzavanje</b> <b>- External Use: Freeze-thaw Resistance</b> 	<b>udovoljava zahtjevima</b> <b>Pass</b>	

Svojstva proizvoda navedenih u točki 1 u skladu su s navedenim svojstvima iz točke 6.  
The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

Ova izjava o svojstvima izdana je pod isključivom odgovornošću proizvođača navedenog u točki 3.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Za i u ime proizvođača potpisao:  
Signed for and on behalf of the manufacturer by:

**Maurizio Mazzotti**  
**(Glavni direktor – Managing Director)**  
Ime i prezime te funkcija - Name and function

*(potpis nečitljiv)*

Spezzano di Fiorano (MO) – ITALIJA, 05.08.2021.

Mjesto i datum izdavanja - Place and date of issue

Potpis – Signature



Tablica - Klizavost (samo kad je propisano)  
Table - Slipperiness (where required by regulation)

Kolekcija Collection	Površine Surfaces	B.C.R.A. Rep. CEC/81 (D.M. 236/1989)	DIN 51097 (CEN/TS 16165, Aneks A)	DIN 51130 (CEN/TS 16165, Aneks B)	UNE-ENV 12633:2006 (CEN/TS 16165, Aneks C)	BS 7976:2002 (CEN/TS 16165, Aneks C)
BLOCK IN	Matte	> 0,40	A+B	R10	CLASE 2 (35 < Rd ≤ 45)	PTV > 36 Dry PTV >36 Wet
BLOCK STR	Textured	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
BLOCK Lastra 20mm	Lastra 20mm	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
	Matte	> 0,40	A+B	R10	CLASE 2 (35 < Rd ≤ 45)	PTV > 36 Dry PTV > 36 Wet
BLOCK NEXT	Grip	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
BREATH	Matte	> 0,40	A	R10	CLASE 1 (15 < Rd ≤ 35)	PTV > 36 Dry PTV = 25+35 Wet
	Grip	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
CODEC	Matte	> 0,40	A+B	R10	CLASE 2 (35 < Rd ≤ 45)	PTV > 36 Dry PTV > 36 Wet
	Grip	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
DIESIS	Matte	> 0,40	A+B	R10	CLASE 2 (35 < Rd ≤ 45)	PTV > 36 Dry PTV > 36 Wet
	Grip	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
DIESIS Lastra 20mm	Lastra 20mm	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
	Matte	> 0,40	A+B	R10	CLASE 2 (35 < Rd ≤ 45)	PTV > 36 Dry PTV > 36 Wet
EXIGO	Glazed Matte	> 0,40	A	R9	CLASE 1 (15 < Rd ≤ 35)	PTV > 36 Dry PTV = 25+35 Wet
	Matte	> 0,40	A+B	R10	CLASE 2 (35 < Rd ≤ 45)	PTV > 36 Dry PTV > 36 Wet
FLUX	Grip	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
FLUX Lastra 20mm	Lastra 20mm	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet
KAVA STR	Textured	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV >36 Wet

KAVA	Lastra	> 0.40	A+B+C	R11	CLASE 3	PTV > 36 Dry
Lastra 20mm	20mm	Tabla - Klizavost (samo kad je propisano)			(Rd > 45)	PTV > 36 Wet
Table - Slipperiness (where required by regulation)						

**Tablica - Klizavost (samo kad je propisano)**  
**Table - Slipperiness (where required by regulation)**

Kolekcija Collection	Površine Surfaces	B.C.R.A. Rep. CEC/81 (D.M. 236/1989)	DIN 51097 (CEN/TS 16165, Aneks A)	DIN 51130 (CEN/TS 16165, Aneks B)	UNE-ENV 12633:2006 (CEN/TS 16165, Aneks C)	BS 7976:2002 (CEN/TS 16165, Aneks C)
<b>LEGEND</b>	<b>Matte</b>	> 0,40	A	R9	CLASE 1 (15 < Rd ≤ 35)	PTV > 36 Dry PTV < 24 Wet
	<b>Grip</b>	> 0,40	A+B+C	R11	CLASE 3 (Rd > 45)	PTV > 36 Dry PTV > 36 Wet
<b>REALM</b>	<b>Matte</b>	> 0,40	A	R10	CLASE 1 (15 < Rd ≤ 35)	PTV > 36 Dry <del>PTV = 25-35 Wet</del>
<b>WARP Floor</b>	<b>Matte</b>	> 0,40	A	R10	CLASE 1 (15 < Rd ≤ 35)	PTV > 36 Dry PTV = 25-35 Wet
<b>ZONE</b>	<b>Matte</b>	> 0,40	A	R9	CLASE 1 (15 < Rd ≤ 35)	PTV > 36 Dry PTV < 24 Wet